

Specifications

Designation					
Protection 1 paire + blindage	DLA-170	DLA-48D3	DLA-24D3	DLA-12D3	DLA-06D3
Protection 2 paires + blindage	DLA2-170	DLA2-48D3	DLA2-24D3	DLA2-12D3	DLA2-06D3
Part number	P82960A P82970A	P82961A P82971	P82962A P82972	P82963A P82973	P82964A P82974A
Network	RTC, ADSL2, VDSL2	RNIS, T0, Ligne 48V	4-20mA	RS232 RS485	RS422
Nominal voltage (Un)	150 V	48V	24V	12V	6V
Voltage max (Uc)	170V	53V	28V	15V	8V
Current max. (Ii)	300 mA	300 Ma	300 Ma	300 mA	300 mA
Impulse current (Iimp) on wave 10/350 μ s -	5kA	5kA	5kA	5kA	5kA
Nominal impulse current (In) On wave 8/20 μ s -	5kA	5kA	5kA	5kA	5kA
Max. discharge current I _{max} On wave 8/20 μ s -1 choc	20kA	20kA	20kA	20kA	20kA
Protection level In (Up)	220V	70V	40V	30V	20V
frequency max.	> 10 MHz	> 3 MHz	> 3 MHz	> 3 MHz	> 3 MHz

Mechanical characteristics

Connection

by screw 0.4 – 1.5 mm² max

Mounting

DIN rail 35mm

Operating temperature

-40°C /+85°C

Plastic

Thermoplastique UL94-V0

