

Type 1 + 2 SPD

DGI 440

Designation

Part number

Electrical characteristics

Technology

Number of pole

Network nominal voltage

Neutral configuration

Max. AC operating system

Temporary Over Voltage (TOV)

Temporary Over Voltage (TOV)

Leakage current

Follow current

Impulse current by pole

Max. withstand 10/350µs

Nominal discharge current

15 x 8/20µs impulses

Max. discharge current

Max. withstand @ 8/20µs

Protection level (@In)

Admissible short-circuit current

DGI 440

P8308H

MOV

One pole (1)

230/400 V

IT - TN C1 mode

TT – TNS C2 mode with DI module for N/PE

440 Vac

580 Vac/5 s withstand

770 Vac/120mn disconnection

< 3 mA

None

50 kA

50 kA

200 kA

2,2 kV

50 000 A



Associated disconnectors

Thermal disconnector

Fuses

Installation ground fault breaker

internal

Fuses type gG – 500 A max.

Type "S" or delayed

Mechanical characteristics

Connection

Disconnection indicator

Remote signaling of disconnection

Mounting

Operating temperature

Ingress Protection

Conformité aux normes

IEC 61 643-11 (Internationale) Low voltage SPD – test class I and II

NF EN 61 643-11 (France) Parafoudres basse tension – essais classe I et II

by screw : 6-35 mm² / by bus

mechanical indicator

output on changeover contact

DIN rail 35mm

-40°C / +85°C

IP20



V : High energy MOV

MI : Disconnection indicator

Ft : Thermal fuse

t° : Thermal disconnection mechanism

C : Contact for remote signaling



Made
In
Safety

©INDELEC SA – 61 Chemin des postes DOUAI (FR) - Tel +33 327 944 952 - www.indelec.com

Indelec

Non contractual document - INDELEC reserves the right to modify its product design, dimensions, weight as well as the illustrations without prior notice.