

Type 1 + 2 SPD

DGU 440

Designation

Part number

Electrical characteristics

Technology

Number of pole

Network nominal voltage

Neutral configuration

Max. AC operating system

Temporary Over Voltage (TOV)

Temporary Over Voltage (TOV)

Leakage current

Follow current

Impulse current by pole

Max. withstand 10/350 μ s

Nominal discharge current

15 x 8/20 μ s impulses

Max. discharge current

Max. withstand @ 8/20 μ s

Protection level (@In)

Admissible short-circuit current

U_C

UT

UT

I_{pe}

I_f

I_{imp}

I_n

I_{max}

U_p

I_{scrr}

DGU 440

P8321H

MOV

One pole (1)

230/400 V

IT – TN C1 mode

TT – TNS C2 mode with DE module for N/PE

440 Vac

580 Vac/5 s withstand

770 Vac/120mn disconnection

< 2 mA

None

25 kA

25 kA

140 kA

1,5 kV

50 000 A

Associated disconnectors

Thermal disconnector

Fuses

Installation ground fault breaker

internal

Fuses type gG – 315 A max.

Type "S" or delayed

Mechanical characteristics

Connection

Disconnection indicator

Remote signaling of disconnection

Mounting

Operating temperature

Ingress Protection

by screw : 6-35 mm² / by bus

mechanical indicator

output on changeover contact

DIN rail 35mm

-40°C/+85°C

IP20

Standards compliance

IEC 61 643-1 (international) Low voltage SPD – test class I and II

EN 61 643-11 (Europe) Low voltage SPD – test class I and II

NF EN 61 643-11 / UL1449 ed.4

V : High energy MOV

MI : Disconnection indicator

Ft : Thermal fuse

t* : Thermal disconnection mechanism

C : Contact for remote signaling

